



11 Publication number:

0 384 758 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 90301910.7

(51) Int. Cl.5: H04L 12/56

2 Date of filing: 22.02.90

3 Priority: 22.02.89 JP 40199/89

② Date of publication of application: 29.08.90 Bulletin 90/35

Designated Contracting States:
DE FR GB

Date of deferred publication of the search report:
 30.10.91 Bulletin 91/44

7) Applicant: KABUSHIKI KAISHA TOSHIBA

72, Horikawa-cho Saiwai-ku Kawasaki-shi Kanagawa-ken 210(JP)


Inventor: Katsube Yasuhiro, c/o Intellectual Property Div. K.K. Toshiba, 1-1 Shibaura 1-chome, Minato-ku Tokyo 1005(JP)

Representative: Freed, Arthur Woolf et al MARKS & CLERK 57-60 Lincoln's Inn Fields London WC2A 3LS(GB)

Call admission control method and cell flow monitoring method in the same method.

(57) In a network in which all of information from terminals (1, 2, ...) having various traffic characteristics are transmitted/switched by a fixed length block including a virtual channel id, a terminal (1) requesting communication declares destination address information and traffic characteristics of the requested communication upon set-up to a network (15). The exchange (15) in the network expresses traffic characteristics of an individual terminal j and an offered load (estimated cell flow) in the network as follows. That is, the traffic characteristics of each terminal i are expressed as a maximum cell flow a(j,i) (i = 1, 2, ..., n) generated from the terminal in time units Δt -(i) (i = 1, 2, ..., n) having n predetermined lengths. The predicted offered load of the line supposing that a new request call is accepted is expressed as an estimated cell flow A (i) (i = 1, 2, ..., n) predicted to be transmitted to the line in the time unit $\Delta t(i)$ by using traffic characteristic values a(j,i) (i = 1, 2, ..., n and j = 1, 2, ..., k, k+1) of the calls j (j = 1, 2, ..., k)currently transitting on the line and a new request call k+1. In a call admission control method, the estimated cell flow A'(i) is compared with an admissible maximum allowable cell flow of line Amax(I) obtained from a circuit capacity, thereby determining "accept" or "reject" of admission of the request call. In a cell flow monitoring method, a cell flow generated from a terminal j in time units $\Delta t(i)$ (i = 1, 2, ..., n) having a plurality of lengths is counted in a

plurality of time units $\Delta t(i)$. If a cell flow in any one time unit $\Delta t(i)$ exceeds a traffic characteristic value a(j,i) grasped beforehand by a network, "violation" is determined for the terminal j, and a regulation sequence is performed.





EUROPEAN SEARCH REPORT

EP 90 30 1910

	Citation of document will	th indication, where appropriate,	T .	elevant	CLASSIFICATION OF THE
tegory		vant passages		o claim	APPLICATION (Int. Cl.5)
X	CONFERENCE RECORD C COMMUNICATIONS CONF lywood, Florida, 28th Nover 1, pages 7.1.1 - 7.1.5; G.M. tion control framework for h transport" * Page 7.1.2, section 3 - page 7.1.3, section 4 - page 7.1.4	ERENCE AND EXHIBTION mber - 1st December 1988, WOODRUFF et al.: "A conigh-speed integrated packet pa	, Hol- vol. ges- tized	3	H 04 L 12/56
X	PROCEEDINGS OF THE IN ON SUBSCRIBER LOOPS 11th - 16th September 1988 KOWALK et al.: "The "polic access in ATM networks" * Section 4, pages 12.2.4 -	AND SERVICES, Boston, M B, pages 12.2.1 - 12.2.6; W. cing function" to control use	IA,		
A	US-A-4 611 322 (LARSON * Abstract; figure 1; column 		51 *	2	
					TECHNICAL FIELDS SEARCHED (Int. Cl.5)
					H 04 L
:	The present search report has t	oeen drawn up for all claims			
	Place of search Date of completion of search				Examiner
	The Hague	02 August 91			ALI A.M.A.Y.
Y: A: O:	CATEGORY OF CITED DOCL particularly relevant if taken alone particularly relevant if combined wit document of the same catagory technological background non-written disclosure intermediate document theory or principle underlying the in	h another (the filing d cocument document	ate cited in th cited for o	ther reasons